

Knit

Design by Meike Harde

Form, materiality and tangibility collide with the Knit collection. Its texture is magnetic, calling out for us to touch its surface, to feel its warmth and to keep it close. Light seeps outwards through the fabric and downwards through a translucent screen, softening its luminosity.

Pendants



7450

Finishes
● 24/ __ Beige M1
(NCS S 2005-Y50R)

LED temperature colour
/1 _ 2700 K 
CRI >90 4752 lm 198 lm/W

Control
7450 __ / _ 1
DALI
7450 __ / _ 3
1-10V
7450 __ / _ Z
Casambi

Electrical connection
Surface
_18 Free Wire
_23 Built-in
_31 Remote
Micro
for plaster
ceilings
_32 Remote
XXS
for all types
of drop
ceilings



Materials
Fabric Shade: Flame-retardant polyester.
Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
Diffuser ring and support: ABS.

Light Source and electronics
6 x LED 5,9W 350 mA
Constant Current 1050 mA
110-240V 50/60Hz

Packaging
1 Box 0,55 x 0,55 x 0,65 m
Vol 0,196 m³
Gross weight 6 Kg Net weight 3,7 Kg

Notes
Extra cable length, 16,00 €/m


LED  IP20   

1160 10 / 1A _18

Model
 Finish
 LED temperature colour
 Control
 Electrical connection
 Only for pendants



7455



Finishes
 ● 24/ _ _ Beige M1
 (NCS S 2005-Y50R)

LED temperature colour
 /1_ 2700 K
 CRI >90 4752 lm 198 lm/W

Control
 7455 _ _ / _ 1
 DALI

7455 _ _ / _ 3
 1-10V

7455 _ _ / _ Z
 Casambi

Materials

Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.

Light Source and electronics

6 x LED 5,9W 350 mA
 Constant Current 1050 mA
 110-240V 50/60Hz

Packaging

1 Box 0,54 x 0,54 x 0,41 m
 Vol 0,119 m³
 Gross weight 5,9 Kg Net weight 3,4 Kg


Notes

Extra cable length. 16,00 €/m

Electrical connection

Surface
 _18 Free Wire
 _23 Built-in
 _31 Remote
 Micro
 for plaster
 ceilings
 _32 Remote
 XXS
 for all types
 of drop
 ceilings

7460



Finishes
 ● 24/ __ Beige M1 (NCS S 2005-Y50R)

LED temperature colour
 /1 _ 2700 K CRI >90 4752 lm 198 lm/W

Control
 7460 __ / _ 1 DALI

7460 __ / _ 3 1-10V

7460 __ / _ Z Casambi

Materials
 Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.


Light Source and electronics
 6 x LED 5,9W 350 mA
 Constant Current 1050 mA
 110-240V 50/60Hz

Packaging
 1 Box 0,54 x 0,54 x 0,41 m
 Vol 0,119 m³
 Gross weight 5,2 Kg Net weight 3,2 Kg

Notes
 Extra cable length. 16,00 €/m

Electrical connection
 Surface
 _18 Free Wire
 _23 Built-in
 _31 Remote Micro for plaster ceilings
 _32 Remote XXS for all types of drop ceilings

7470



Finishes
 ● 24/ __ Beige M1 (NCS S 2005-Y50R)

LED temperature colour
 /1 _ 2700 K CRI >90 4752 lm 198 lm/W

Control
 7470 __ / _ 1 DALI

7470 __ / _ 3 1-10V

7470 __ / _ Z Casambi

Materials
 Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.


Light Source and electronics
 6 x LED 6,7W 400 mA
 Constant Current 1200 mA
 110-240V 50/60Hz

Packaging
 1 Box 0,77 x 0,77 x 0,50 m
 Vol 0,296 m³
 Gross weight 9,4 Kg Net weight 4,9 Kg

Notes
 Extra cable length. 16,00 €/m

Electrical connection
 Surface
 _18 Free Wire
 _23 Built-in
 _31 Remote Micro for plaster ceilings
 _32 Remote XXS for all types of drop ceilings

7475



Finishes
 ● 24/ __ Beige M1 (NCS S 2005-Y50R)

LED temperature colour
 /1 _ 2700 K CRI >90 4752 lm 198 lm/W

Control
 7475 __ / _ 1 DALI

7475 __ / _ 3 1-10V

7475 __ / _ Z Casambi

Materials
 Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.

Light Source and electronics
 6 x LED 6,7W 400 mA
 Constant Current 1200 mA
 110-240V 50/60Hz

Packaging
 1 Box 0,78 x 0,78 x 0,59 m
 Vol 0,358 m³
 Gross weight 9 Kg Net weight 5,6 Kg

Notes
 Extra cable length. 16,00 €/m

Electrical connection
 Surface
 _18 Free Wire
 _23 Built-in
 _31 Remote Micro for plaster ceilings
 _32 Remote XXS for all types of drop ceilings



Electrical connection options for models 7450 / 7455 / 7460 / 7470 / 7475

Choose your preferred installation option according to your needs.
For each composition, the optimal minimum number of drivers will be delivered.

Drop ceiling

The innovative remote and built-in fittings accentuate the silkiness and lightness of compositions on suspended ceilings, its great visual grandeur taking center stage.

For Ref. 7450 / 7455 / 7460 / 7470 / 7475

Remote



Micro ø 3 cm
height 7 cm
for plaster ceilings.
Black finish.





XXS ø 6 cm
height 6 cm
for all types of drop
ceilings. Match with
fixture finish.

Built-in



ø 8 cm
height 6 cm
match with
fixture finish.



Regular ceiling

When architecture does not allow for performance, surface and free wire showcase possibilities for any need or desire with no limits, ideal for both individual or cluster arrangements.

For Ref. 7450 / 7455 / 7460 / 7470 / 7475

Surface



ø 16 cm
match with
fixture finish.

Free Wire



1 wire





2 - 3 wires



4 wires


ø 22 cm ø 36 cm ø 40 cm
you can choose the finish of the canopy
among black, white or any colour
matching one of the pendants.



Knit

Floor



1160 10 / 1AModel
Finish
LED temperature colour
Control**7480**

Finishes
● **24/** _ _ Beige M1
(NCS S 2005-Y50R)

LED temperature colour
/1 _ 2700 K
CRI >90 4752 lm 198 lm/W

Control
7480 _ _ / _ 5
Push

7480 _ _ / _ Z
Casambi

Materials

Fabric Shade: Flame-retardant polyester.
Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
Diffuser ring and support: ABS. Floor stemp: Iron steel.
Floor base: Zamak.

Light Source and electronics


6 x LED 5,9W 350 mA
Constant Voltage 42V 1,43mA
110-240V 50/60Hz

Packaging

2 Boxes
Box 1: 0,54 x 0,54 x 0,41 m
Box 2: 0,38 x 1,71x 0,36 m
Total Vol. 0,3529 m³
Gross weight 18,8 Kg Net weight 11,3 Kg

Notes

Electric cable 2,5 m

7485

Finishes
● **24/** _ _ Beige M1
(NCS S 2005-Y50R)

LED temperature colour
/1 _ 2700 K
CRI >90 4752 lm 198 lm/W

Control
7485 _ _ / _ 5
Push

7485 _ _ / _ Z
Casambi

Materials

Fabric Shade: Flame-retardant polyester.
Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
Diffuser ring and support: ABS. Floor stemp: Iron steel.
Floor base: Zamak.

Light Source and electronics


6 x LED 5,9W 350 mA
Constant Voltage 42V 1,43mA
110-240V 50/60Hz

Packaging

2 Boxes
Box 1: 0,54 x 0,54 x 0,41 m
Box 1: 0,38 x 1,71x 0,36 m
Total Vol. 0,3529 m³
Gross weight 28,4 Kg Net weight 17,7 Kg

Notes

Electric cable 2,5 m

7487

Finishes
● **24/** _ _ Beige M1
(NCS S 2005-Y50R)

LED temperature colour
/1 _ 2700 K
CRI >90 4752 lm 198 lm/W

Control
7487 _ _ / _ 5
Push

7487 _ _ / _ Z
Casambi

Materials

Fabric Shade: Flame-retardant polyester.
Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
Diffuser ring and support: ABS. Floor stemp: Iron steel.
Floor base: Zamak.

Light Source and electronics

6 x LED 5,9W 350 mA
Constant Voltage 42V 1,43 mA
110-240V 50/60Hz


Packaging

2 Boxes
Box 1: 0,78 x 0,78 x 0,59 m
Box 2: 0,45 x 0,46 x 1,93 m
Total Vol. 0,7579 m³
Gross weight 30 Kg Net weight 18,5 Kg

Notes

Electric cable 2,5 m

7490



Finishes
 ● 24/ __ Beige M1
 (NCS S 2005-Y50R)

LED temperature colour
 /1 _ 2700 K 
 CRI >90 4752 lm 198 lm/W






Control
 7490 __ / _ 5
 Push
 7490 __ / _ Z
 Casambi

Materials
 Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.


Light Source and electronics
 6 x LED 5,9 W 350 mA
 Constant Voltage 42V 1,43 mA
 110-240V 50/60Hz

Packaging
 1 Box 0,55 x 0,55 x 0,65 m
 Vol 0,196 m³
 Gross Weight 5,4 Kg Net Weight 3,3 Kg

Notes
 Electric cable 2,5 m

7492



Finishes
 ● 24/ __ Beige M1
 (NCS S 2005-Y50R)

LED temperature colour
 /1 _ 2700 K 
 CRI >90 4752 lm 198 lm/W






Control
 7492 __ / _ 5
 Push
 7492 __ / _ Z
 Casambi

Materials
 Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.


Light Source and electronics
 6 x LED 5,9 W 350 mA
 Constant Voltage 42V 1,43 mA
 110-240V 50/60Hz

Packaging
 1 Box 0,78 x 0,78 x 0,59 m
 Vol 0,358 m³
 Gross Weight 7,3 Kg Net Weight 4,5 Kg

Notes
 Electric cable 2,5 m

7494



Finishes
 ● 24/ __ Beige M1
 (NCS S 2005-Y50R)

LED temperature colour
 /1 _ 2700 K 
 CRI >90 4752 lm 198 lm/W






Control
 7494 __ / _ 5
 Push
 7494 __ / _ Z
 Casambi

Materials
 Fabric Shade: Flame-retardant polyester.
 Interior diffuser: Polyethylene. Bottom diffuser: Methacrylate.
 Diffuser ring and support: ABS.

Light Source and electronics
 6 x LED 5,9 W 350 mA
 Constant Voltage 42V 1,43 mA
 110-240V 50/60Hz

Packaging
 1 Box 0,80 x 0,80 x 0,75 m
 Vol 0,48 m³
 Gross Weight 14,3 Kg Net Weight 5,9 Kg

Notes
 Electric cable 2,5 m

1160 10 /1A

Model Finish
LED temperature colour
Control

