# **PANZERI**

# Zero

#### 220-240V AC ON-OFF

A03501.100.0401

# white



#### Data sheet

CODE	A03501.100.0401
SYSTEM POWER CONSUMPTION	20W
EFFICACY	61.35lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1980lm
LUMEN OUTPUT	1227lm
EFFICIENCY	62%
WEIGHT	2,40 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS (CM)	10,0 x 108,0 x 7,0



Ceiling or wall lighting fixture for interiors, with direct and indirect light emission. gold leaf coating, or in polished stainless steel.

Specular aluminium reflector.

Cover in brass with white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or with galvanic chrome plating.

Extruded polycarbonate diffuser with opaline finish.







## Technical drawing



## **Application**



### Polar diagram

