



SPALY51P
Design by Ryosuke Fukusada

Collection consisting of aluminium suspended lamps.
Available in several colours and sizes.


Typology: SUSPENSION LAMP

Ratings

- Built in line voltage **LED** module
- CCT 3000 K, 2700 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off dimmable trailing edge
- Die cast aluminium body, painted
- Opalescent diffuser

SP ALY 51 P

kg 3.7 m³ 0.11



Product code composition

ALYSOID


Type	Article	Colours	Catene / chains	Source
SP	ALY 51 P	AN anthracite grey wrinkled	NI black polished nickel OT natural brass	LED 15W - diffused beam 3000K*, 2700K upon request




IP20 CRI90 220-240VAc **LED** ~1375 lm* ~92 lm/W*

example composition code SP ALY51P AN OT LED

Available colors



OT
Anthracite grey and natural brass



NI
Anthracite grey and black polished nickel

CUSTOMER _____ NOTES _____

SPALY51PAN __ LED

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.