



FA FAIRY

Design by Manuel Vivian

Collection consisting of recessed downlights, wall lamps, ceiling lamps and suspended lamps with chromed metal frame and glass diffuser. Available in several colours and sizes. Built-in (dimmable for some versions) LED light source.

Typology: recessed

Ratings

- •Built in ED module
- Diffused light
- ·Surface installation in ceiling cut-out
- •Supply constant current 350mA
- •Switch mode: on-off
- •Aluminum ring, chrome

| | | Product of | code composition | | | |
|---|----------------|------------|--------------------|-------------------|--------------------|-------------------------|
| FAIRY / DRIVER NOT INCLUDED | | | | | | |
| | | Type | Article | Colours | Finish | Source |
| | | | | | | |
| | kg 1 m³ 0.0014 | FA | FAIRY X | CS crystal | CR chrome | LED 6,2W - 350mA |
| Ø 8 cm | | | | | | diffused beam - 2700K |
| 6.3 gm | Ø 9 cm | | | AM amber | | ı |
| | | | | GR grey | | |
| Ø 9 cm | | CE | with dedicated IP2 | 20 CRI90 L | D ~565 lm 9 | 1 lm/W |
| foro - hole Ø 8 cm / profondità min - min depth 10 cm - Collegare in serie. / Wire in series. | | | | | | |
| example composition code FA FAIRYX AM CR LED | | | | | | |
| | | 9- | | | | |

For optional accessories/drivers or dimming technology please refer to our pricelist, website or contact our

Available colors







representatives

CS Crystal

AM Amber

GR Grey

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

| | CUSTOMER | NOTES |
|----------------|----------|-------|
| FAFAIRYX CRLED | | |
| | | |

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.