



PLURBANG
Design by Dima Loginoff


Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes.

Typology: CEILING

- Ratings
- Built in **LED** module
 - Supply voltage: 220-240 Vac
 - CCT 2700K, 3000K* or 3500K
 - IP20
 - Surface installation over holes
 - Dimmable PHASE CUT
 - Aluminum body painted
 - Diffuser opalescent

kg 1,7 m³ 0,025

Product code composition



URBAN / DRIVER INCLUDED

Type	Article	CCT	CODE	Colours	LED Source
PL	URBAN G	1 2700K	X	BC wrinkled white	LCC 17,5W - diffused beam
		2 3000K*		BR matt bronze	
		3 3500K		NI matt nickel	

IP20 CRI90 220-240V_{AC} **LED** ~2200 lm* 125 lm/W*
 example composition code **PL URBANG 1 X NI LCC**

Available colors



BC
Wrinkled
white

BR
Matt
bronze

NI
Matt
nickel

PLURBANG_X__LCC

CUSTOMER _____ NOTES _____

NOTICE:
Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.