



SPURBANP

De sign by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.


Available in several colours and sizes.

Typology: SUSPENSION LAMP

Ratings

- •Built in LED module
- •Supply voltage: 220-240 Vac
- •CCT 2700K, 3000K* or 3500K
- •IP20
- Surface installation over holes
- •Dimmable PHASE CUT
- ·Aluminum body painted
- •Diffuser opalescent

kg 1,9 m³ 0,02



Product code c omposition

URBAN / DRIVER INCLUDED

ONDAIL / BRIVER INCESSES						
	Туре	Article	ССТ	CODE	Colours	LED Source
	SP	URBAN P	1 2700K	х	BC wrinkled white	LCC 17,5W - diffused beam
			2 3000K*		BR matt bronze	
			3 3500K		NI matt nickel	

(€ ⊕ IP20 CRI90





220-240VAC LED ~2200 lm* 125 lm/W*

example composition code SP URBANP 1 X NI LED





white



BR Matt bronze



NI Matt nickel

SPURBANP_X _ LCC

CUSTOMER

NOTES

NOTICE: Luminous flux (Im) and efficacy (Im/W) for a II LED luminaires is based on nominal ratings of the LED sources. Techn ical data could be subject to alteration without not ice. Axo Light does not provide legal guarantee for the a ccuracy of this data sheet.