



SP URBA PI

Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.

Available in several colours and sizes.


Typology: RECESSED SUSPENSION LAMP

Ratings

- •Built in line voltage ED module
- •CCT 3000 K
- Downlight
- •Ceiling cut-out installation
- •Supply voltage ~220-240V
- ·Switch mode: on-off, dimmable trailing edge
- •Die cast aluminium body, painted
- Opalescent diffuser

SPURBAPI (RECESSED) kg 1,7 m³ 0,02

Product code composition



URBAN / solo con illuminazione verso il basso / downward lighting only									
	Туре	Article	Colours		Finishing	:	Source		
	SP	URBA P I	BC	wrinkled	xx		LED	15W - diffused beam	
	31	ORBATI		white	XX		LLD	3000K*	
								2700K	
			BR	matt bronze					
			NI	matt nickel					
	(€ ⊕ IP20 CRI90 dimmake railing edge 220-240VAC ■ED ~1375 Im* ~92 Im/W*								
foro - $hole 1 \times \emptyset 3 \text{ cm} + 2 \times \emptyset 1,4 \text{ cm} / profondità min - min depth 10 \text{ cm}$									

example composition code SP URBAPI BR XX LED



white





BR Matt bronze



NI Matt nickel

SPURBAPI _ _ XXLED

CUSTOMER

NOTES

NOTICE: Luminous flux (Im) and efficacy (Im/W) for all built in LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.