



PLURBMIM
Design by Dima Loginoff


Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes.

Typology: CEILING

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off, dimmable trailing edge
- Aluminium body, painted
- Diffuser

PL URBMI M
kg 0,5 m³ 0,02



Product code composition
URBAN MINI

Type	Article	Colours	Finishing	Source
PL	URB MI M	BC wrinkled white BR matt bronze NI matt nickel	XX	LED 8W - diffused beam 2700K 4000K

220-240VAC **LED** (~640 lm* ~80 lm/W* 3000K*)
 example composition code **PL URBMI M BR XX LED**

Available colors



BC
Wrinkled
white

BR
Matt
bronze

NI
Matt
nickel

CUSTOMER _____ NOTES _____
 PLURBMIM _ _ XXLED _____

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.