URBAN MINI - PL URB MI G - technical sheet





PLURBMIG

Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.


Available in several colours and sizes Built-in dimmable

Typology: CEILING

Ratings

- •Built in LED module
- •Supply voltage: 220-240 Vac •CCT 2700K, 3000K* or 3500K
- •IP20
- Surface installation over holes
- •Dimmable PHASE CUT
- ·Aluminum body painted
- Diffuser opalescent

PL URBMI G kg 0,8 m³ 0,025



Product code composition

URBAN / DRIVER INCLUDED

Туре	Article	ССТ	CODE	Colours	LED Source
PL	URBMI G	1 2700K	x	BC wrinkled white	LCC 6,5 W - diffused beam
		2 3000K*		BR matt bronze	
		3 3500K		NI matt nickel	





example composition code PL URBMIG1X NI LCC

Available colors







Matt bronze



Matt nickel

CUSTOMER	
OOOIOMEIK	

NOTES

PLURBMI G_ X __ LCC

NOTICE:

Luminous flux (Im) and efficacy (Im/W) for all LED luminaires is based on nominal ratings of the LED sources.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.