URBAN MINI - PL URB MI G - technical sheet





PLURBMIG

Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.

Available in several colours and sizes Built-in dimmable

Typology: CEILING

Ratings

- •Built in line voltage LED module
- •CCT 3000 K
- Downlight
- •Surface installation over holes
- Supply voltage ~220-240V
- •Switch mode: on-off, dimmable trailing edge
- •Aluminium body, painted
- Diffuser

PL URBMI G kg 0,8 m³ 0,025



Product code composition

URBAN MINI

Туре	Article	Colours	Finishing	Source	
PL	URB MI G	BC wrinkled white	xx	LED	8W - diffused beam 2700K
		BR matt bronze			40000
		NI matt nickel			
	 	l -∕-∮l	LED	l	

Example composition code PL URBMIG BR XX LED (~640 lm* ~80 lm/W* 3000K*)

Available colors







BC Wrinkled white

BR Matt bronze

NI Matt nickel

CUSTOMER	NOTES

NOTICE:

PLURBMIG _ _ XXLED

Luminous flux (Im) and efficacy (Im/W) for all LED luminaires is based on nominal ratings of the LED sources.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.