



**SPVEL070**  
Design by Manuel Vivian

Collection of ceiling and suspended lamps. The radial diffuser and light covering are treated with a flame-retardant (Glow wire 960 °C and 750°C respectively). Available in several colours and sizes.


Typology: SUSPENDED

Ratings

- E27
- Downlight and uplight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Steel frame, painted
- Radial cone diffuser in pongé fabric and light covering in jersey

**SP VEL 070**

kg 6.5 m<sup>3</sup> 0.48



Product code composition

VELVET / diffusore INCLUSO / diffuser INCLUDED

Type	Article	Colours (lampshade)	Colour (Radial diffuser)	Source
SP	VEL 070 E27	BC ice white	BC white	E27 1 x Max 20W LED or 1 x Max 70W halogen
		BA ivory white	GI gold yellow	
		BL blue	MA brown	
		MA brown	MT brick red	
		NE black	NE black	

CE IP20 +LED 220-240V<sub>ac</sub>  
example composition code SP VEL070E27 NE BW



Equivalent Sound Absorption Area (A) in m<sup>2</sup> per lamp


FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,15	0,44	0,51	0,66	0,73	0,75	1,01	0,61	0,63

Available lampshade colors



BC Ice white    BA Ivory white    BL Blue    MA Brown    NE Black

Available radial diffuser colors



BC White    BW Warm white

SPVEL070E27 \_\_\_\_\_ CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.