Wireflow free-form

0356

Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. The electrical connection point can be positioned on the ceiling or wall.

Model Sheet





ø 36 cm

СЗ 200

Finish	O4 Black RAL 9005	Lightin
LED temperature color	2700 K	Lamp f the ligh
Dimming	DALI 1-10V PUSH Optional Casambi Min. quantity, upcharge and extra lead time apply [EN]	
Instalation type	Surface Canopy	Photor
Materials	Ceiling rose: Steel Body: Aluminum Rods: Steel	Efficien Coordi Total F Maxim
Light source	7 x LED 4,48W 350mA D	
LED	CRI>80 3432 lm 109 2700 K	
Driver	CC - Constant Current 350 110~240 V 50/60 HZ	
	Dimmable LED (IP20) Bi-volt 50-60Hz	
Application	Hanging lamps	
Packaging	1 Box	
	Gross weigth 7 Net weigth 6	

ng effect

ral Lighting for general lighting that equally distributes ht in all directions.

3 | \land



metric Data

40.11% ency dinate System CG 3432 Flux mum Value 53.92

Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

165 cm

80,5 cm 11 cm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U. Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971 Spain / Portugal T +34 934 796 970 customer.service@vibia.com vibia.com