## Algorithm




Design By Toan Nguyen



## Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Graphite ADAPTA RF 9913 WX



2700 K

LED temperature color

DALI 1-10V Push Casambi Optional Min. quantity, upcharge and extra

lead time apply [EN]

Instalation type

Surface Canopy

Materials

Dimmina

Sphere: Blown glass Glass fastening: Aluminum Diffuser: Polycarbonate Pendant structure: Steel

Light source

29 x LED 3,15W 1050mA

F

LED

CRI>80 9056 lm 99 2700 K

Driver

CC - Constant Current 1050 100~240 V 50/60 HZ

Remarks

Request built-in canopy at www.vibia.com

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the

cables.







IP20 Bi-volt 50-60Hz

Application

Hanging lamps

**Packaging** 

0.67 m x 0.59 m x 0.54 m Gross weigth 25

Net weigth 20.5 Vol. 0.6254

## Lighting effect

## **General Lighting**

Lamp for general lighting that equally distributes the light in all directions



Photometric Data

**Total Flux** 

9056 lm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty