
## Algorithm




Design By Toan Nguyen



## Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

18 Graphite ADAPTA RF 9913 WX



93 White RAL 9016

LED temperature color

2700 K

Dimmina

DALI 1-10V Push Optional Casambi

Min. quantity, upcharge and extra lead time apply [EN]

Instalation type

Surface Canopy

Materials

Sphere: Blown glass Glass fastening: Aluminum Diffuser: Polycarbonate Pendant structure: Steel

Light source

15 x LED 3,15W 1050mA

F

LED

CRI>80 4685 lm 99 2700 K

Driver

CC - Constant Current 1050 100~240 V 50/60 HZ

Remarks

Request built-in canopy at

www.vibia.com

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the





IP20 Bi-volt 50-60Hz

Application

Hanging lamps

**Packaging** 

1.177 m x 0.686 m x 0.18 m Gross weigth 17.9 Net weigth 13.75 Vol. 0.2663

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes the light in all directions



Photometric Data

**Total Flux** 

4684 lm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty