Halo lineal

\vee | 3 | \wedge

2341

Design By Martín Azúa

HALO is a hanging lamp with three intertwined, straight pieces, which creates subtle, magical lighting. Designed by Martín Azúa. By combining different pieces you can show off hanging lights which float in the air to fit harmoniously into the room. It is available in matt white lacquer.

Model Sheet





LED temperature color 3000 K Dimming 1-10V Optional DALI or Community, upcharge of lead time apply [EN] Instalation type Surface Canopy Materials Diffuser: PMMA Ceiling rose: Steel Light source 3 x LED STRIP 24V 15,3 A LED CRI>80 3851 Im 85.57 3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi Image: Four Dimeter Diffuser: Dimeter Diffuser: A LED CRI>80 3851 Im 85.57 3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi Image: Four Dimeter Diffuser Diffuser: Dimeter Diffuser Application Hanging lamps Packaging 2 Box 1.265 m x 0.19 m x 0.13 Gross weigth 7.3 Net weigth 6.57 Vol. 0.0463	
Optional DALI or Co. Min. quantity, upcharge of lead time apply [EN] Instalation type Surface Canopy Materials Diffuser: PMMA Ceiling rose: Steel Light source 3 x LED STRIP 24V 15,3 A LED CRI>80 3851 Im 85.57 3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi Image: The provide the second secon	
Materials Diffuser: PMMA Ceiling rose: Steel Light source 3 x LED STRIP 24V 15,3 A LED CRI>80 3851 lm 85.57 3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi Image: The provided of the provided o	
Ceiling rose: Steel Light source 3 x LED STRIP 24V 15,3 A LED CRI>80 3851 lm 85.57 3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi Image: The Dimmable intermediate inte	
A LED CRI>80 3851 lm 85.57 3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi	
3000 K Driver CV - Constant Voltage Object] 100-240 V 50. Remarks 1-10V Electronic dimmi	W
Object] 100~240 V Šo. Remarks 1-10V Electronic dimmi IP20 Bi-volt 50-60H: IP20 Bi-volt 50-60H: Packaging 2 Box 1.265 m x 0.19 m x 0.13 Gross weigth 7.3 Net weigth 6.57	
E Dimmable LE IP20 Bi-volt 50-60H Application Hanging lamps Packaging 2 Box 1.265 m x 0.19 m x 0.13 Gross weigth 7.3 Net weigth 6.57	
Packaging 2 Box 1.265 m x 0.19 m x 0.13 Gross weigth 7.3 Net weigth 6.57	:D
1.265 m x 0.19 m x 0.13 Gross weigth 7.3 Net weigth 6.57	
	m

Lighting effect

General Lighting Lamp for general lighting that equally distributes the light in all directions.




Photometric Data Efficiency Coordinate System


Maximum Value

Total Flux

60.85 lm/W CG 3472.02 lm 699.21 cd

Other Applications





Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty