ORIGAMI

Design by Ramón Esteve.



Reference

4504.

Application

Wall Lamps

Installation type

Surface

Description

ORIGAMI blends light functionality with an opportunity for artistic creation. With just two pieces, designers can create infinite compositions. With a single connection point between the pieces and simple surface mounting installation, you can make as many configurations as you desire. ORIGAMI lighting is rated for both outdoor (IP65) and indoor settings which you can construct to climb a wall or façade like ivy. The light source is LED, guaranteeing high-efficiency energy consumption.

Diffuser

Polycarbonate diffuser

Materials

Shade: ABS Arm: Polycarbonate Wall plate: Polycarbonate

Finish



4504-10 White (NCS S 0300-N)



4504-29 Brown D1 (NCS S 8005-Y50R)




4504-38 Terra Dark (NCS S 5040-Y70R)



4504-53 Green M1 (NCS S 6005-G80Y)

Sketch



Electrical characteristics

2 x LED STRIP 6,3W 350mA

2 x LED PLATE 6,3W 350mA



Total 25.2 W



Light source: 2700K CRI > 80756 Im 120 Im/W

Fixture: 854 lm 68 lm/W

Driver included: CC - Constant Current 350 mA 220-240V 50/60Hz

Electronic dimming TRIAC

Technical characteristics

- A maximum of 30 modules can be connected to a single connection point. For bigger compositions, check connection system.

×

Physical characteristics

2 Box / 0.26 x 0.51 x 0.51 m. / Vol. 0.1002 m³ / Gross weight 3.9 kg. / Net weight 3.5 kg.

Installation and assembly

Please, see the installation manual


Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.







Certificates









