Brooklyn Round

220-240V AC dimmable (DALI/Push DIM) L23101.180.0402

Data sheet


CODE	L23101.180.0402
SYSTEM POWER CONSUMPTION	29W
EFFICACY	51.14lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3420lm
LUMEN OUTPUT	1483lm
EFFICIENCY	43.4%
WEIGHT	1,89 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	12,0 x 110,0 x 55,0 cm



Suspension lighting fixture for interiors, with direct light emission. Bended extruded aluminium structure in white, black or mat brass polyacrylic paint. Extruded polycarbonate diffuser with opaline finish. Galvanized sheet metal end caps in polyacrylic paint. Suspension kit with griplocks and 2m (78,7") long steel cables. 2,2m (86,6") long power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and covering in white polyacrylic paint.


CE EAE 🗵


Technical drawing



Polar diagram

white





Brooklyn Round

Accessories / power supply

ХМ150/24 DIM СЕ III 🗵	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
XM60/24 DIM	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	No. of
CE ERE 🗵		900 220 mm 8 %**

Brooklyn Round

Accessories / power supply and fixing

XM23101.538.0099

CE ERE 🗵

Canopy for power supply with 8 outputs and to join 7 steel cables, for up to 8 Brooklyn Round models maximum.



Brooklyn Round

Accessories / fixing

XM231/23201L

Plate for multiple suspensions.





