Brooklyn Round

220-240V AC dimmable (DALI/Push DIM)

Data sheet

| CODE | L23102.360.0402 |
|----------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION | 55W |
| EFFICACY | 53.91lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B20) 80.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 6840lm |
| LUMEN OUTPUT | 2965lm |
| EFFICIENCY | 43.3% |
| WEIGHT | 3,24 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| GLOW WIRE TEST PERFORMANCE | 850° |
| PACKING DIMENSIONS | 107,0 x 107,0 x 11,0 cm |

black







Suspension lighting fixture for interiors, with direct light emission. Bended extruded aluminium structure in white, black or mat brass polyacrylic paint. Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 2m (78,7") long steel cables. 2,2m (86,6") long power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and covering in white polyacrylic paint.

CE ERE 🗵

Technical drawing



Polar diagram



Brooklyn Round

Accessories / power supply

| хм150/24 DIM С є ЕНГ 🗵 | LED driver, 150W 24V DC, DALI/Push DIM dimmable. | |
|---------------------------|--|---|
| XM60/24 DIM | LED driver, 60W 24V DC, DALI/Push DIM dimmable. | State and State |
| CE ERI 🗵 | | قاری 229 mm 8 % * |

Brooklyn Round

Accessories / power supply and fixing

XM23102.538.0099

CE ERE 🗵

Canopy for power supply with 8 outputs and to join 7 steel cables, for up to 8 Brooklyn Round models maximum.



Brooklyn Round

Accessories / fixing

XM231/23202L

Plate for multiple suspensions.





