# PANZERI

## To-be


220-240V AC ON-OFF L02617.065.0501

### Data sheet

| CODE                     | L02617.065.0501     |
|--------------------------|---------------------|
| SYSTEM POWER CONSUMPTION | 7W                  |
| EFFICACY                 | 51.86lm/W           |
| LIGHT SOURCE             | LED                 |
| LIGHT SOURCE LIFETIME    | L70 (B50) 60.000h   |
| COLOUR TEMPERATURE       | 2700K Ra>90         |
| LIGHT DISTRIBUTION       | diffused            |
| POWER SUPPLY             | 220-240V AC         |
| FREQUENCY                | 50/60Hz             |
| ELECTRICAL CONFIGURATION | ON-OFF              |
| DRIVER                   | integrated included |
| NOMINAL LUMINOUS FLUX    | 546lm               |
| LUMEN OUTPUT             | 363lm               |
| EFFICIENCY               | 66.5%               |
| WEIGHT                   | 0,78 Kg             |
| PROTECTION DEGREE        | IP40                |
| COLOUR TOLLERANCES       | SDCM 3              |
| PACKING DIMENSIONS (CM)  | 8,0 × 141,0 × 8,0   |



#### **Technical drawing**







Suspension lighting fixture for interiors, with direct light emission. Extruded aluminium structure in white, mat black, bronze or mat brass polyacrylic paint or with gold leaf coating. Extruded aluminium heat sink. Modelled polycarbonate diffuser with opaline finish. Turned brass end cap in polyacrylic paint.

2m (78,7") long suspension and power cable in transparent PVC.

Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering in white, mat black, bronze or mat brass polyacrylic paint or with gold leaf coating.

### Polar diagram

