# **PANZERI**

## Viisi

### 220-240V AC dimmable (DALI/Push DIM)

T02002.210.0402





#### Data sheet

CODE	T02002.210.0402
SYSTEM POWER CONSUMPTION	44W
EFFICACY	54lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	5180lm
LUMEN OUTPUT	2376lm
EFFICIENCY	45.9%
WEIGHT	6,94 Kg
PROTECTION DEGREE	IP40
PACKING DIMENSIONS (CM)	0,0 x 0,0 x 0,0



Floor lighting fixture for interiors, with indirect light emission.

Pickled sheet metal bearing base in polyacrylic paint.

Machined aluminium structure in white or black polyacrylic paint.

Anodized extruded aluminium heat sink.

Extruded polycarbonate diffuser with opaline finish.

Push-button to adjust luminosity.


Equipped with a 2,3m (90,6") long power cable in transparent PVC with plug.








## Technical drawing





## Polar diagram

