# **PANZERI**

## Viisi

#### 220-240V AC dimmable (DALI/Push DIM)





#### Data sheet

| CODE                     | L02102.210.0402          |
|--------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION | 44W                      |
| EFFICACY                 | 54lm/W                   |
| LIGHT SOURCE             | LED                      |
| COLOUR TEMPERATURE       | 3000K Ra>90              |
| LIGHT DISTRIBUTION       | diffused                 |
| POWER SUPPLY             | 220-240V AC              |
| FREQUENCY                | 50/60Hz                  |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER                   | integrated included      |
| NOMINAL LUMINOUS FLUX    | 5180lm                   |
| LUMEN OUTPUT             | 2376lm                   |
| EFFICIENCY               | 45.9%                    |
| WEIGHT                   | 3,00 Kg                  |
| PROTECTION DEGREE        | IP40                     |
| PACKING DIMENSIONS (CM)  | 14,0 x 224,0 x 14,0      |
|                          |                          |



Suspension lighting fixture for interiors, with indirect light emission.

 $\label{lem:machined} \mbox{Machined aluminium structure in white or black polyacrylic paint.}$ 

Anodized extruded aluminium heat sink.

Extruded polycarbonate diffuser with opaline finish.

Suspension kit with griplocks and 2m (78,7") long steel cables.

2,3m (90,6") long power cable in transparent PVC.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal  $% \left( 1\right) =\left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right$ covering in white or black polyacrylic paint.







## Technical drawing



## Polar diagram

