# **PANZERI**

## Zero Round

24V DC

M03301.075.0410





### Data sheet

CODE	M03301.075.0410
SYSTEM POWER CONSUMPTION	34W
EFFICACY	89.97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	4252lm
LUMEN OUTPUT	3059lm
EFFICIENCY	71.9%
WEIGHT	1,12 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS (CM)	83,0 x 83,0 x 10,0



Single or multiple suspension lighting fixture for interiors, with direct and indirect light

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.

Suspension kit with griplocks and 5m (196,9") long steel cables.

5m (196,9") long power cable in transparent PVC.


Provided without power canopy.







### Technical drawing



### Polar diagram

