



**PLURBANP**  
Design by Dima Loginoff


Collection consisting of aluminium ceiling lamps and suspended lamps.  
Available in several colours and sizes.

Typology: CEILING

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off dimmable trailing edge
- Die cast aluminium body, painted
- Opalescent diffuser

**PL URBAN P**  
kg 1,6 m³ 0,02



Product code composition

URBAN


Type	Article	Colours	Finishing	Source
PL	URBAN P	BC wrinkled white BR matt bronze NI matt nickel	XX	LED 15W – diffused beam 3000K* 2700K

220-240VAc **LED** ~1375 lm\* ~92 lm/W\*  
 example composition code **PL URBANP NI XX LED**


Available colors



**BC**  
Wrinkled  
white



**BR**  
Matt  
bronze



**NI**  
Matt  
nickel

PLURBANP \_ \_ XXLED

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

\_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.