PANZERI

Bella


220-240V AC dimmable (Step DIM) A05201.011.0509

Data sheet

CODEA05201.011.0509SYSTEM POWER CONSUMPTION5WEFFICACY77.6lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460lmLUMEN OUTPUT388lmEFFICIENCY84.3%VEIGHT0.56 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3		
EFFICACY77.6lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460lmLUMEN OUTPUT388lmEFFICIENCY94.3%WEIGHT0,56 KgPROTECTION DEGREEIP20	CODE	A05201.011.0509
LIGHT SOURCELEDLIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460ImLUMEN OUTPUT388ImEFFICIENCY84.3%WEIGHT0,56 KgPROTECTION DEGREEIP20	SYSTEM POWER CONSUMPTION	5W
LIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460lmLUMEN OUTPUT388lmEFFICIENCY84.3%WEIGHT0,56 KgPROTECTION DEGREEIP20	EFFICACY	77.6lm/W
COLOUR TEMPERATURE 2700K Ra>90 LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	LIGHT SOURCE	LED
LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460Im LUMEN OUTPUT 388Im EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	COLOUR TEMPERATURE	2700K Ra>90
FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	LIGHT DISTRIBUTION	adjustable
ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	POWER SUPPLY	220-240V AC
DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	ELECTRICAL CONFIGURATION	dimmable (Step DIM)
LUMEN OUTPUT 388Im EFFICIENCY 84.3% WEIGHT 0,56 Kg PROTECTION DEGREE IP20	DRIVER	integrated included
EFFICIENCY 84.3% WEIGHT 0.56 Kg PROTECTION DEGREE IP20	NOMINAL LUMINOUS FLUX	460lm
WEIGHT 0,56 Kg PROTECTION DEGREE IP20	LUMEN OUTPUT	388lm
PROTECTION DEGREE IP20	EFFICIENCY	84.3%
	WEIGHT	0,56 Kg
COLOUR TOLLERANCES SDCM 3	PROTECTION DEGREE	IP20
	COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS (CM) 12,0 x 24,0 x 13,0	PACKING DIMENSIONS (CM)	12,0 x 24,0 x 13,0



Technical drawing



white





Ceiling or wall lighting fixture for interiors, with swivelling light beam. Galvanized sheet metal ceiling or wall bracket. Die-cast aluminium wall plate in white, black, bronze, mat brass or titanium polyacrylic paint. Turned brass joints in polyacrylic paint. Die-cast aluminium structure in polyacrylic paint. Die-cast aluminium head rotating on three axes in polyacrylic paint. Modelled acrylic diffuser with mat finish. Aluminium closing disk in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort.

Polar diagram