PANZERI

Bella

220-240V AC dimmable (Step DIM)

A05230.011.0509





Data sheet

| CODE | A05230.011.0509 |
|--------------------------|---------------------|
| SYSTEM POWER CONSUMPTION | 5W |
| EFFICACY | 77.6lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B10) 70.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | adjustable |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (Step DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 460lm |
| LUMEN OUTPUT | 388lm |
| EFFICIENCY | 84.3% |
| WEIGHT | 0,56 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS (CM) | 12,0 x 24,0 x 13,0 |
| | |



Ceiling or wall lighting fixture for interiors, with swivelling light beam.

Galvanized sheet metal ceiling or wall bracket.

 $\hbox{\it Die-cast aluminium wall plate in white, black, bronze, mat brass or titanium polyacrylic}$

Turned brass joints in polyacrylic paint.

Die-cast aluminium structure in polyacrylic paint.

Die-cast aluminium head rotating on three axes in polyacrylic paint.

Modelled acrylic diffuser with mat finish.


Aluminium closing disk in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort.






Technical drawing







Polar diagram