PANZERI

Bella


220-240V AC dimmable (Step DIM) C05201.011.0509


Data sheet

| CODE | C05201.011.0509 |
|--------------------------|---------------------|
| SYSTEM POWER CONSUMPTION | 5W |
| EFFICACY | 77.6lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B10) 70.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | adjustable |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (Step DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 460lm |
| LUMEN OUTPUT | 388lm |
| EFFICIENCY | 84.3% |
| WEIGHT | 0,84 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS (CM) | 17,0 x 40,0 x 16,0 |
| | |



Technical drawing





120 mm - 4 ¾"



white





Table lighting fixture for interiors, with swivelling light beam. Pickled sheet metal bearing base in polyacrylic paint. Body in tapered steel tube in white, black, bronze, mat brass or titanium polyacrylic paint. Turned brass joint in polyacrylic paint. Die-cast aluminium structure in polyacrylic paint. Die-cast aluminium swivelling head in polyacrylic paint. Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort. Equipped with a 1,4m (55,1") long power cable with jack connector and adapter plug.

Polar diagram

