PANZERI

Viisi

Data sheet

SYSTEM POWER CONSUMPTION

CODE

EFFICACY

LIGHT SOURCE

COLOUR TEMPERATURE

ELECTRICAL CONFIGURATION

NOMINAL LUMINOUS FLUX

LIGHT DISTRIBUTION

POWER SUPPLY

LUMEN OUTPUT

PROTECTION DEGREE

PACKING DIMENSIONS (CM)

EFFICIENCY

WEIGHT

FREQUENCY

DRIVER

220-240V AC dimmable (DALI/Push DIM) L02101.210.0402

L02101.210.0402

44W

LED

54lm/W

diffused

50/60Hz

5180lm

2376lm

45.9%

3,00 Kg

14,0 x 224,0 x 14,0

IP40

3000K Ra>90

220-240V AC

dimmable (DALI/Push DIM)


integrated included

INDIRECT LIGHT

Suspension lighting fixture for interiors, with indirect light emission. Machined aluminium structure in white or black polyacrylic paint. Anodized extruded aluminium heat sink. Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 2m (78,7") long steel cables. 2,3m (90,6") long power cable in transparent PVC. Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in white or black polyacrylic paint.

CE ERE 🗵

Technical drawing



Polar diagram

white

