# **PANZERI**

## App

#### 220-240V AC ON-OFF

A09819.002.0406





#### Data sheet

CODE	A09819.002.0406
SYSTEM POWER CONSUMPTION	36W
EFFICACY	79.5lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2862lm
LUMEN OUTPUT	2862lm
EFFICIENCY	100%
WEIGHT	2,03 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS (CM)	28,0 x 37,0 x 16,0




Wall lighting fixture for interiors, with indirect light emission. Die-cast aluminium wall bracket in polyacrylic paint. Extruded aluminium structure in white, mat brass or titanium polyacrylic paint.








### Technical drawing



### Polar diagram



# **PANZERI**

## App

### Accessories / source - power supply

XM14/230

CE EHE 🗵

Dimmable device for 230V LED modules, 5÷100W.

