

PH 4/3 Pendant

The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of metal and painted white to ensure uniform, comfortable light distribution.



Product info

Mounting

Suspension type: Cable 3x0,75mm². Canopy: Yes. Cable length: 3m.

Finish

White, powder coated.

Materials

Shades: Spun aluminium. Anti-glare disc: White, spun aluminium.

Sizes and weights

Width x Height x Length (mm) | 400 x 200 x 400 Max 1.1 kg

Class

Ingress protection IP20. Electric shock protection I w. ground.

Specification notes

The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louispuolsen.com we update a list of recommendable light sources.

Light source

1x60W E27



Product family



PH 4/3 Table

Product variants

Light source

1x60W E27

Product description

Suspended metal luminaire.
Iconic design.
Part of a wide family of multiple sizes.

Mounting

Can be mounted on 4" octagonal junction box. (USA only)

Light description

Glare free, mostly downlight distribution.

Design

Poul Henningsen

Material

Shades: spun aluminium, 2mm (0.08") thick, white powder coated, semi-gloss exterior and matte interior for diffuse light.
Stem of spun aluminium, 2mm (0.08") thick, white powder coated.
Glare shield of sheet aluminium, 2mm (0.08") thick, white powder coated. Removable for re-lamping by tool-less spring tabs.
Socket: Porcelain, medium base for A-19, frosted envelope lamps.
Socket position is adjustable to allow correct lamp position and fixture illumination.
Canopy: 5.3" diameter x 0.9" tall cone of spun aluminium.
Cable: white PVC coated, 12 ft. (USA)

Weight

1.129

Finish

White

