PANZERI

Hilow Line

220-240V AC dimmer on cable T10919.200.0522

Data sheet

CODET10919.200.0522SYSTEM POWER CONSUMPTION39WEFFICACY69.59lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL70 (B10) 60.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONdiffusedPOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmer on cableDRIVERintegrated includedNOMINAL LUMINOUS FLUX4032lmLUMEN OUTPUT2714lmEFFICIENCY67.3%WEIGHT10.16 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3PACKING DIMENSIONS13.0 x 222.0 x 13.0 cm		
EFFICACY69.59lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL70 (B10) 60.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONdiffusedPOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmer on cableDRIVERintegrated includedNOMINAL LUMINOUS FLUX4032lmLUMEN OUTPUT2714lmEFFICIENCY67.3%WEIGHT10.16 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3	CODE	T10919.200.0522
LIGHT SOURCELEDLIGHT SOURCE LIFETIMEL70 (B10) 60.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONdiffusedPOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmer on cableDRIVERintegrated includedNOMINAL LUMINOUS FLUX4032lmLUMEN OUTPUT2714lmEFFICIENCY67.3%WEIGHT10.16 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3	SYSTEM POWER CONSUMPTION	39W
LIGHT SOURCE LIFETIMEL70 (B10) 60.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONdiffusedPOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmer on cableDRIVERintegrated includedNOMINAL LUMINOUS FLUX4032lmLUMEN OUTPUT2714lmEFFICIENCY67.3%WEIGHT10.16 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3	EFFICACY	69.59lm/W
COLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONdiffusedPOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmer on cableDRIVERintegrated includedNOMINAL LUMINOUS FLUX4032lmLUMEN OUTPUT2714lmEFFICIENCY67.3%WEIGHT10,16 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3	LIGHT SOURCE	LED
LIGHT DISTRIBUTIONdiffusedPOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmer on cableDRIVERintegrated includedNOMINAL LUMINOUS FLUX4032lmLUMEN OUTPUT2714lmEFFICIENCY67.3%WEIGHT10.16 KgPROTECTION DEGREEIP20COLOUR TOLLERANCESSDCM 3	LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmer on cable DRIVER integrated included NOMINAL LUMINOUS FLUX 4032lm LUMEN OUTPUT 2714lm EFFICIENCY 67.3% WEIGHT 10.16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	COLOUR TEMPERATURE	2700K Ra>90
FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmer on cable DRIVER integrated included NOMINAL LUMINOUS FLUX 4032lm LUMEN OUTPUT 2714lm EFFICIENCY 67.3% WEIGHT 10,16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	LIGHT DISTRIBUTION	diffused
ELECTRICAL CONFIGURATION dimmer on cable DRIVER integrated included NOMINAL LUMINOUS FLUX 4032lm LUMEN OUTPUT 2714lm EFFICIENCY 67.3% WEIGHT 10.16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	POWER SUPPLY	220-240V AC
DRIVER integrated included NOMINAL LUMINOUS FLUX 4032lm LUMEN OUTPUT 2714lm EFFICIENCY 67.3% WEIGHT 10,16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX 4032lm LUMEN OUTPUT 2714lm EFFICIENCY 67.3% WEIGHT 10.16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	ELECTRICAL CONFIGURATION	dimmer on cable
LUMEN OUTPUT 2714lm EFFICIENCY 67.3% WEIGHT 10,16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	DRIVER	integrated included
EFFICIENCY 67.3% WEIGHT 10,16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	NOMINAL LUMINOUS FLUX	4032lm
WEIGHT 10,16 Kg PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	LUMEN OUTPUT	2714lm
PROTECTION DEGREE IP20 COLOUR TOLLERANCES SDCM 3	EFFICIENCY	67.3%
COLOUR TOLLERANCES SDCM 3	WEIGHT	10,16 Kg
	PROTECTION DEGREE	IP20
PACKING DIMENSIONS 13,0 x 222,0 x 13,0 cm	COLOUR TOLLERANCES	SDCM 3
	PACKING DIMENSIONS	13,0 x 222,0 x 13,0 cm



mat brass


Floor lighting fixture for interiors, with indirect light emission. Bearing base in black marquina marble.

Extruded aluminium structure in white, mat black, bronze or mat brass polyacrylic paint. Die-cast aluminium end caps in polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.

Equipped with a 3m (118,1") long power cable with switch to adjust luminosity and plug.

Technical drawing



INDIRECT LIGHT