Halo wall


\vee | 3 | \wedge

2361

Design By Martín Azúa

Wall sconce. The light rods, anchored to an aluminium profile are arranged around a central perpendicular axis, in parallel or angled. The modular character allows for large interconnected lights murals to be configured.

Model Sheet



Finish	11 Black NCS S 8500N
	13 Off-White NCS S 1000-N
LED temperature color	3000 K
Dimming	1-10V Optional DALI or Casambi Min. quantity, upcharge and extra lead time apply [EN]
Instalation type	Surface Canopy
Materials	Diffuser: Methacrylate LED support: Aluminum Wall support: Aluminum
Light source	3 x LED STRIP 24V 15,3W A+
LED	CRI>80 4584.12 lm 99.87 3000 K
Driver	CV - Constant Voltage [object Object] 220~240 V 50/60 HZ
Remarks	Surface
	Dimmable LED
	IP20 50-60Hz 1-10V
Application	Wall Lamps
Packaging	1 Box 2.25 m x 0.158 m x 0.158 m Gross weigth 3.2 Net weigth 1.4 Vol. 0.0561

Lighting effect

General Lighting Lamp for general lighting that equally distributes the light in all directions.

1	
 1	-

Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U. Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971 Spain / Portugal T +34 934 796 970

customer.service@vibia.com vibia.com