

Structural

VIBIA





2600

Design By Arik Levy

Wall light with basic lines and cubic volumes that form sculptures integrated into the architecture.

Model Sheet




Finish	21 Black Grey NCS S 7000-N 15 Grey L2 NCS S 2500-N
LED temperature color	3000 K / 3500 K / 4000 K
Dimming	DALI / CASAMBI / 1-10V
Installation type	Surface Canopy
Materials	Body: Aluminum Diffuser: Polycarbonate Profile: Aluminum
LED	 CRI>90 3000 K / 3500 K / 4000 K
Driver	Constant Voltage 110-240 V V 50-60 Hz HZ
Remarks	Only one main input by square box 16x16cm.   Dimmable LED IP20 Bi-volt 50-60Hz 
Application	Wall Lamps
Packaging	1 Box 0.265 m x 0.265 m x 0.165 m Gross weight 1.5 Net weight 1.1 Vol. 0.0115

Lighting effect

General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric Data

Efficiency	100.00%
Coordinate System	CG
Total Flux	176.90 lm
Maximum Value	159.34 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com