


## 2634

Design By Arik Levy

Ceiling light with basic lines and cubic volumes that form sculptures integrated into the architecture.

### Model Sheet




<b>Finish</b>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 12px; height: 12px; background-color: black; border-radius: 50%; margin-right: 5px;"></span> 21 Black Grey NCS S 7000-N</li> <li><span style="display: inline-block; width: 12px; height: 12px; background-color: grey; border-radius: 50%; margin-right: 5px;"></span> 15 Grey L2 NCS S 2500-N</li> </ul>
<b>LED temperature color</b>	3000 K
<b>Dimming</b>	1-10V <b>Optional</b> DALI or Casambi Min. quantity, upcharge and extra lead time apply [EN]
<b>Installation type</b>	Surface Canopy
<b>Materials</b>	Body: Aluminum Diffuser: Polycarbonate Profile: Aluminum
<b>LED</b>	CRI>90 3000 K
<b>Driver</b>	CV - Constant Voltage [object Object] 110-240 V 50/60 HZ
<b>Remarks</b>	Main input by the biggest box
	<div style="display: flex; justify-content: space-between; align-items: center;"> <span> </span> <span>Dimmable</span> <span>LED</span> </div> <div style="display: flex; justify-content: space-between; align-items: center; margin-top: 5px;"> <span>IP20</span> <span>Bi-volt</span> <span>50-60Hz</span> <span></span> </div>
<b>Application</b>	Ceiling Lamps
<b>Packaging</b>	1 Box 0.38 m x 0.61 m x 0.22 m Gross weight 5.2 Net weight 4.7 Vol. 0.0509

#### Lighting effect

##### General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



#### Photometric Data

<b>Efficiency</b>	74.12 lm/W
<b>Coordinate System</b>	CG
<b>Total Flux</b>	3126.51 lm
<b>Maximum Value</b>	1320.72 cd

#### Other Applications



All of our products come with a five-year warranty.  
Check our legal terms at [www.vibia.com/warranty](http://www.vibia.com/warranty)