Mayfair mini



5495


Design By Diego Fortunato

Portable version powered by a rechargeable battery. This can be moved exactly where needed, indoors or out. A push button in the base turns it on and off and controls dimmina

Model Sheet







25 Beige D1 NCS S 4005-Y50R

23 Warm White NCS S 0502-Y50R

47 Green L1 NCS S 4005-G80Y

37 Terra Red

LED temperature color

2700 K

Dimming

Sensor

Instalation type

Surface Canopy

Materials

Shade: ABS

Diffuser: Polycarbonate Vertical tube: Steel

Base: ABS

Light source 1 x undefined

CRI>90 175 lm 70 LED

2700 K

Driver CV - Constant Voltage [object

Object] 100~240 V 50/60 HZ

Rechargeable battery autonomy. Remarks

6 hours maximum intensity. 12 hours 50% intensity. 24 hours 25%

Bi-volt 50-60Hz

Application

Table Lamps

Packaging

0.26 m x 0.25 m x 0.5 m Gross weigth 1.62 Net weigth 0.73 Vol. 0.0325

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency Coordinate System **Total Flux** Maximum Value

86.077 lm/ CG 223 lm 365.58 cd/klm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty