



Design By Ramos & Bassols

The Spa wall or ceiling lamp projects a bright glare-free light thanks to the subtle fluted effect of its shade. The aluminium frame has a wide range of finishes to adapt to different interior designs.

## Model Sheet



Finish

25 Beige D1 NCS S 4005-Y50R



11 Black NCS S 8500-N



23 Warm White NCS S 0502-Y50R

LED temperature

2700 K / 3500 K

Dimming

1-10V / DALI / CASAMBI

Instalation type

Remote basic

Materials

Diffuser: Methacrylate Body: Aluminum Ceiling rose: Aluminum


LED

E CRI>90 1510 lm 119,87

Driver

2700 K / 3500 K

Constant Current 600 220~240 V V 50~60 Hz HZ







**Application** 

Ceiling Lamps

**Packaging** 

1 Box 1.5 m x 0.1 m x 0.1 m Gross weigth 3 Net weigth 1.8 Vol. 0.015

## Lighting effect

## **General Lighting**

Lamp for general lighting that equally distributes the light in all directions.



## Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency Coordinate System Total Flux Maximum Value

61.06 lm/W CG

644.16 lm 275.08 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

65,5 cm

121,2 cm