





Design By Ramos & Bassols

The Spa wall or ceiling lamp is suitable for damp areas. Its versatile system enables the luminaries to be placed in a line to illuminate up to two metres and a half of wall or ceiling space.

# Model Sheet





23 Warm White NCS S 0502-Y50R



25 Beige D1 NCS S 4005-Y50R



11 Black NCS S 8500-N

LED temperature

2700 K / 3500 K

Dimming

DALI / 1-10V

Instalation type

Remote basic

Materials


Diffuser: Methacrylate Body: Aluminum Ceiling rose: Aluminum

LED

E CRI>90 3020 lm 119,8 2700 K / 3500 K

Driver

Constant Current 600 220~240 V V 50~60 Hz HZ











Ceiling Lamps

**Packaging** 

1 Box 1.5 m x 0.1 m x 0.1 m Gross weigth 2.9 Net weigth 1.8 Vol. 0.015

### Lighting effect

## **General Lighting**

Lamp for general lighting that equally distributes the light in all directions.



### Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency Coordinate System Total Flux Maximum Value

60.79 lm/W CG 1286.38 lm

549.33 cd

### Other Applications



253 cm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

6,6 cm