





Design By Ramos & Bassols

The Spa wall lamp is ideal for damp areas. The softness of polycarbonate and its linear grooves contrast with the matt texture of the aluminium frame.

Model Sheet





11 Black NCS S 8500-N



25 Beige D1 NCS S 4005-Y50R



23 Warm White NCS S 0502-Y50R

LED temperature

2700 K / 3500 K

Dimming

1-10V / DALI

Instalation type

Remote basic

Materials

Diffuser: Methacrylate Body: Aluminum Ceiling rose: Aluminum

Light source

1 x LED STRIP 21,6W 600mA



LED


CRI>90 3212 lm 57,61 2700 K / 3500 K

Driver

Constant Current 600 220~240 V V 50~60 Hz HZ













Packaging

1 Box 2.3 m x 0.1 m x 0.1 m

Gross weigth 1 Net weigth 1 Vol. 0.023

Wall Lamps

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency Coordinate System 60.77 lm/W CG

1071.98 lm Maximum Value 457.78 cd

Other Applications





212 cm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty